


Galvanically isolated contact bridges



MAX. OPERATING FORCE	N
RELEASE FORCE	0,64
REST POSITION	1
TRIPPING POSITION	a mm
RELEASE POSITION	20,1±0,25
OVER TRAVEL LIMIT	a mm
	16,1±0,25
	a mm
	18,0±0,25
	a mm
	14,1

Only for Cod. SJ11-RNS00BWC

Only for Cod. SJ11-RDS00BWC

EXECUTIONS WITH FIXING DISTANCE 28 mm	
CODE	FEATURE
SJ11-RNS00UW*	MICROSWITCH COMPLETE WITH LEVER - STD.TYPE CONTACTS
SJ11-RNG00UW*	MICROSWITCH COMPLETE WITH LEVER - GOLD PLATE CONTACTS
SJ11-RNS00BW*	MICROSWITCH COMPLETE WITH LEVER - WITH SOLID SILVER CONTACTS AND BLOWING MAGNETS

EXECUTIONS WITH FIXING DISTANCE 58 mm	
CODE	FEATURE
SJ11-RDS00UW*	MICROSWITCH COMPLETE WITH LEVER - STD.TYPE CONTACTS
SJ11-RDGO0UW*	MICROSWITCH COMPLETE WITH LEVER - GOLD PLATE CONTACTS
SJ11-RDS00BW*	MICROSWITCH COMPLETE WITH LEVER - WITH SOLID SILVER CONTACTS AND BLOWING MAGNETS

NOTE : PLACE THE PERMANENT MAGNETS SO THAT THE POLARITIES ARE AS SHOWN IN THE DRAWING

NOTE : 2 µm GOLDEN PLATING

* COVER MATERIAL	
CODE LETTER	MATERIAL
C	PC
N	PA66
P	PEI

SIMBOLI UTILIZZATI PER IDENTIFICARE LA QUOTA IN REVISIONE DI MODIFICA

SIMBOLO UTILIZZATO PER LE QUOTE SOGGETTE A CONTROLLO INTERNO

MODIFICHE	MODIFICHE	MODIFICHE	MODIFICHE	MODIFICHE	MODIFICHE
1 C.M.2381 07-05-99 ABBIATI	2 C.M.2653 31-05-00 ABBIATI	3 D.M.0021 24/10/06 GM	4 D.M.0067 19/04/22 GM	5 D.M.0088 14/06/22 GM	6 C.M. 0001 19/09/24 MU

3	2	1	Rifer.
			Funz.
			Accop.
			Ciente

			MATERIALE	TRATTAMENTO
DATA	15-04-98	15-04-98	15-04-98	
FIRMA	ABBIATI	VELLUTINI	GALLUCCI	
			TOLLERANZE PER DIMENSIONI LINEARI ED ANGOLARI PRIVE DI INDICAZIONI DI TOLLERANZE SPECIFICHE UNI EN 22768-1	SCALA 1:1
			MOLTO GROSSOLANA GROSSOLANA MEDIA FINE	REVISIONE
				① ② ③ ④ ⑤ ⑥
			DESCRIZIONE	COD. VEDI TABELLA
			SNAP-ACTION MICROSWITCH (1 N.O. + 1 N.C.) WITH OPERATION LEVER AND FASTON TERMINALS	DIS.
				IP951300

