


TECHNICAL REQUIREMENTS / CARATTERISTICHE TECNICHE		
ELECTRICAL PROPERTIES/PROPRIETA ELETTRICHE		
AC Working Voltage	kV	24
Dry Frequency Voltage	kV	50
BIL	kV	125
MECHANICAL PROPERTIES/PROPRIETA MECCANICHE		
Tensile	kN	20
Bending	kN	4
Torque	Nm	80
PHYSICAL PROPERTIES/PROPRIETA FISICHE		
Height	mm	220
Dmin	mm	70
Dmax	mm	70
Creepage	mm	305
Material	Epoxy Resin	
Applicable standard / Standard applicabili IEC 60273 IEC 60660 / 60660-1		

3	Material Insert	Brass			
2	Insert	M12			
ITEM No.	DESCRIPTION	MATERIALS QTY REMARK			
EN 22768-1 grado: ☐ Fine ☒ Media ☐ Grossolana ☐ Molto grossolana UNI EN 22768-1 sta's: ☐ Fine ☒ Medium ☐ Coarse ☐ Very coarse					
a tutti i diritti di legge / All rights pertaining to this drawing are reserved for ISOLEX					
		Scala Scale 1:1	Codice Code		
		File			
ation			Revisione Revision	1	A4
			Foglio Sheet	1	di of
Resin Post Insulator H=220 24 kV			Disegno N. - Dwg. No.		
			ID10463		

Undimensioned Tolerance		Cliente Customer
> 3 - 6	± 0.3	ISOLEX ISOLEX Milano Italy
> 6 - 30	± 0.5	
> 30 - 120	± 0.8	
> 120 - 400	± 1.2	
> 400 - 1000	± 2.0	